

Page 1 of 7

TEST REPORT

Applicant: Shenzhen Huafurui Technology Co., Ltd.

Address: Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road,

Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China

Report on the submitted sample said to be:

Sample name: Smartphone

Tested Model No. : KINGKONG STAR 2

Trade mark: CUBOT

Sample Size: 180mm*85mm*13mm

Sample Weight: 412.2g

Manufacturer: Shenzhen Huafurui Technology Co., Ltd.

Country of Origin: China

Sample received date: 2024-07-12

Testing period: 2024-07-12 ~ 2024-07-16

Date of Report: 2024-07-16

Testing Location: 901, No.40 Building, Xialang Industrial Zone, Heshuikou Community, Matian Street,

Guangming District, Shenzhen, Guangdong, China

Category under the WEEE Directive: 2012/19/EU

Signed for and on behalf of LCS

my. luo

Terry.Luo



TRF-4-R-031

A/0

Shenzhen LCS Compliance Testing Laboratory Ltd. Add: 901, No.40 Building, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com Scan code to check authenticity





REQUIREMENT OF RECYCLING AND RECOVERY RATE

According to article 11 and Annex III, below minimum target of Recycling and Recovery rate should be met after 15 August 2018

Category	Product Type	Minimum Recycling Rate	Minimum Recovery Rate	
1	1 Temperature exchange equipment		85%	
2	Screens, monitors and equipment containing screens having a surface greater than 100cm ²	70%	80%	
3 3 110	Lamps	70%	80%	
4	Large equipment(any external dimension more than 50cm) including, but not limited to.	80%	85%	
5	Small equipment(no external dimension more than 50cm) including, but not limited to.	55%	75%	
6	Small IT and telecommunication equipment(no external dimension more than 50cm)	55%	75%	

Recycling & Recovery Rate are calculated as following formulas: Recycling Rate= Recycling Weight Product Total Weight(%)

Recycling Weight + Energy Recovery Weight **Recovery Rate=-**(%)

Product Total Weight

Result of Reuse/Recycling/Recovery Assessment

Reuse/Recycling/Recovery	Reuse/Recycling (%)	Recovery (%)	
Reuse/Recycling/Recovery Targets under the 2012/19/EU WEEE Directive	55%	75%	
Result of Assessment	82.6	82.6	
WEEE Requirement Compliance	PASS	PASS	

Note: Such products belong to Category 5

A/0




TRF-4-R-03






IBC IIII

resting Lab






Page 3 of 7



A/0 Shenzhen LCS Compliance Testing Laboratory Ltd. Add: 901, No.40 Building, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com Scan code to check authenticity








sia I Shenzhen LCS Compliance Testing Laboratory Ltd. Add: 901, No.40 Building, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com Scan code to check authenticity



测股份





1001 ×

esting La



Shenzhen LCS Compliance Testing Laboratory Ltd. Add: 901, No.40 Building, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com Scan code to check authenticity




Photo No.	Component/Material	Weight(g)	Percent Weight(%)	Reuse/Recycling (%)	Energy Recovery (%)	Recovery (%)
A1	Metal	54.9	13.3	12.0	/	12.0
A2	Plastic	182.3	44.2	39.3	/	39.3
A3	РСВ	54.7	13.3	9.3	/	9.3
A4	Battery	65.8	16.0	11.2	/	11.2
A5	Ceramic/Glass	54.5	13.2	10.8		10.8
	Total	412.2	100	(f) 82.6	1	82.6
D:	hly Procedure		Till Maining	rap Na	女子子子子子子子子子子子子子子子子子子子子子子子子子子子子子子子子子子子子	ing Lab


Disassembly Procedure

The disassembly procedure taken here is in accordance with the treatment requirements under the Annex II of the WEEE Directive. In addition, to consider economic and efficiency factors, manual operation and disassembly tools have been applied to separate the components and materials from this product in order to simulate the scenario at the treatment facility, and to achieve the objective that the separated components and materials from this product in order to simulate the scenario at the treatment facility and to achieve the treatment facility, and to achieve the objective that the separated components and materials can be used, recycled and recovered.





Report No.: LCSA07124060R





Note:

Due to their insignificant weight and the difficulty of their separation in a manual operation, sticker, solder, paint and printing material

are not included in this assessment.

Plastic containing brominates flame retardants in not assessed in the list.

Recycling and Recovery Rate Calculation

Reuse Recycling & Recovery Rate using in the report are calculated as following formulas:

Reuse & Recycling Rate = (Reuse & Recycling Weight) /(Product total Weight) (%)

Recovery Rate = (Reuse & Recycling Weight + Energy Recovery Weight)/(Product Total Weight)(%) Total weight of the product is including the main product is including the main product and accessories

ANNEX VII of WEEE Directive

Selective treatment for materials and components of waste electrical and electronic equipment:

- Polychlorinated biphenyls(PCB) containing capacitors in accordance with Council Directive 96/59/PC of 57/ED December 1997 adapting to technical progress Council Directive 67/548/EEC relating to the classification, packaging and labeling of dangerous substances,
- Components containing radioactive substances with the exception of components that are below the exemption thresholds set in Article 3 of and Annex I to council Directive 96/29/Euratom of 13 May 1996 laying down basic safety standards for the protection of the health of workers and the general public against the dangers arising from ionizing radiation
- Electrolyte capacitors containing substances of concern(height>25mm, diameter >25mm or proportionately similar volume)

Recommendations for WEEE Directive Compliance

- In order to avoid the product not meeting the reuse/recycling/recovery targets regulated under the WEEE Directive and the regulations of EU countries, the applicant company should, when selecting material and components design, consider they can be easy to reuse and recycle, this consideration will lessen the impact of the required international environmental directives and also improve the product's competitiveness
- It is recommended that the applicant company, when designing new product, especially where components and material have a large weight ratio, should consider using recyclable materials in order to increase the product's reuse/recycling/recover ration
- The product should apply to the RoHS Directive(Directive 2011/65/EU on the restriction of the use of certain hazardous substance in electrical and electronics equipment), the hazardous substance specification in the Directive should be controlled in the homogenous material of this product

If a product has changed its product design, or materials or components employed, then the product should be reassessed and retested in accordance with the WEEE Directive for reuse/recycling/recovery assessment and RoHS for restricted/banned substances requirements.

TRF-4-R-031 A/0



Shenzhen LCS Compliance Testing Laboratory Ltd. Add: 901, No.40 Building, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com Scan code to check authenticity